

MATERIAL SAFETY DATA SHEET

1. MATERIAL IDENTIFICATION

Product Name: **ACRAN ADHESIVE GEL (RESIN), PART-A**
 Chemical Family: Epoxy Resin Mixture
 Company Name: Eastern Resins Corp.
 1174 River Street
 Woonsocket, RI 02895, USA

BUSINESS PHONE: (401) 769-6700
 EMERGENCY PHONE: (800) 255-3924

2. COMPOSITION

Chemical Name	Wt %	Exposure Limits	
		ACGIH TLV-TWA	OSHA PEL
Epoxy resin Mixture	>70	N/E	N/E
Titanium Dioxide*	<10	10 mg/m ³	15 mg/m ³
Carbon black*	<1	3.5 mg/m ³	3.5 mg/m ³
Fumed silica*	<10	20 mppcf	20mppcf

Specific ingredients are considered a Trade Secret

Abbreviations: N/E - NOT ESTABLISHED

* - Materials are in *Non-Airborne* form

3. HEALTH HAZARDS

Primary Routes of Exposure: Eyes: Yes Skin: Yes Inhalation: Yes

Eye Contact: May cause irritation and swelling.

Skin Contact: May cause irritation and sensitization. Symptoms can be immediate or delayed several hours.

Inhalation: May cause irritation and temporary or permanent sensitization.

Ingestion: May cause irritation.

Other: Preexisting skin sensitization may be aggravated by exposure to this product.

4. FIRST AID MEASURES

Eyes: Flush eyes thoroughly with water for at least 15 minutes while holding eyelids open. Seek medical attention.

Skin: Remove contaminated clothing. Wipe excess from skin and wash the affected area thoroughly with soap and water. Wash contaminated clothing thoroughly before reuse.

Inhalation: Remove to fresh air, and provide oxygen or artificial respiration if needed. Obtain medical attention; symptoms can be delayed up to several hours.

Ingestion: DO NOT induce vomiting. Give 1-2 cups of water or milk unless the person is drowsy, convulsing, or unconscious. Get medical attention.

5. FIRE FIGHTING MEASURES

Flammable Properties: Flash Point: >300°F (PMCC)

Explosive Limits: Not applicable

Auto-Ignition Temperature: Not applicable

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, aldehydes, and other organic substances.

EXTINGUISHING MEDIA AND FIRE FIGHTING INSTRUCTIONS: When sufficiently large quantities are present, firefighters should be equipped with full bunker gear, including a positive pressure, NIOSH approved, self-contained breathing apparatus. Extreme heat or water contamination may cause closed containers to explode.

Extinguishing Media: Use carbon dioxide, dry chemical or appropriate foam

6. ACCIDENTAL RELEASE MEASURES

Ventilate the spill area and evacuate if necessary. Remove all ignition sources. Dike and contain large spills. Clean-up personnel should use adequate protective equipment.

7. HANDLING AND STORAGE

Store in a cool; dry place, in closed containers at room temperature. Avoid contact with incompatible materials. Wear protective eyewear, chemical-resistant gloves, and other protective clothing as appropriate.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Engineering/Ventilation Controls: Effective engineering controls should be used whenever possible to eliminate and/or reduce worker exposure to all respiratory hazards. General ventilation, local ventilation, or isolation may prove adequate to keep airborne concentrations below exposure limits.

Respiratory Protection: Not required under normal conditions in a well-ventilated workplace.

Skin Protection: Impervious gloves and protective clothing should be worn as necessary.

Eye Protection: Chemical splash goggles or safety glasses with side shields should be worn as appropriate.

9. STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions and use.

Conditions and Materials to Avoid: Reacts with amines and strong oxidizing agents.

Hazardous Polymerization: Will not occur.

10. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odor:	Gray Paste, slight ether odor	Boiling Point:	Not determined
Vapor Pressure (mm Hg):	<1 @25°C	Vapor Density (air=1):	>1
Specific Gravity:	1.2-1.3	Solubility in Water:	None

11. TOXICOLOGICAL INFORMATION

This section provides toxicological information with regard to the pure form of the component indicated. It is suggested that persons trained in its evaluation interpret this information.

Epoxy Resins:	Acute Oral LD₅₀ (Rat):	11.4 g/kg
	Acute Dermal LD₅₀ (Rabbit):	>20 g/kg

12. DISPOSAL CONSIDERATIONS

Keep out of surface waters, sewers, and waterways entering or leading to surface waters. Notify authorities if any exposure to the environment occurs or is likely to occur. Utilize an appropriate disposal facility, in compliance with applicable federal, state, and local environmental control regulations.

13. TRANSPORTATION INFORMATION

DOT/IATA Proper Shipping Name: Not Regulated

14. REGULATORY INFORMATION

TSCA: The chemical components of this product are included in the TSCA Chemical Substance Inventory, as required.

SARA TITLE III:

Section 313 – Toxic Chemicals: None

Section 311/312 – Hazard Categories:

Fire Hazard:	No	Reactivity Hazard:	No
Sudden Release of Pressure Hazard:	No	Immediate (Acute) Health Hazard:	Yes
Delayed (Chronic) Health Hazard:	No		

OSHA Hazard Communication Standard Hazard Classes:

NFPA Hazards: Health: 2	Flammability: 1	Reactivity: 0
HMIS Hazards: Health: 2	Flammability: 1	Reactivity: 0

This information is furnished without warranty, expressed or implied, except that it is accurate to the best of our knowledge. The data on this sheet relates only to the specific material designated herein. **Eastern Resins Corp.** assumes no legal responsibility for use or reliance upon these data.